Wood Inputs Survey

You are completing this for CSO (Central Statistics Office)

If the company details or structure have changed contact us on (01) 4984213 or email forestry@cso.ie

The Wood Inputs Survey is an annual survey of the domestic use of wood removals from forests in Ireland. The main focus of the survey is the purchases by enterprises located in Ireland of roundwood and non-roundwood from forest owners in Ireland. The survey scope includes any use of the wood removals by the forest owners themselves e.g. to manufacture woodchip. The survey does not collect information on exports or imports of wood and wood products. The results of the survey will be used by the CSO for statistical purposes such as compiling supply and use tables.

Please use the following definitions for the roundwood removals questions:

Large sawlog: Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres. They are used for the manufacture of sawn timber largely for use by the construction industry.

Small sawlog (palletwood): Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres are classified as small sawlog (palletwood). It is suitable for use as packaging and for making garden furniture.

Stakewood: Roundwood with a top diameter of between 7-13 cm and a typical length of between 1.5 and 1.9 metres should be classified as stakewood if it is to be used for stakes and fencing.

Pulpwood: Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Pulpwood is used to produce pulp, door panels, particle board, oriented strand board (OSB), medium-density fibreboard (MDF), and other fibreboard. Pulpwood that has been converted to woodchip onsite should be entered in the Woodchip category.

Roundwood purchased for use as biomass: All roundwood removals for energy biomass use should be included in this category. If the roundwood was chipped at the forest then include it under Woodchip. Please include removals under the *Forestry for Fibre* scheme if the roundwood was removed to be used as biomass.

Q1.1 Use of coniferous roundwood removals from publicly-owned forests in Ireland.

Please provide the quantity delivered to your premises in tonnes overbark at actual moisture content. If you have the roundwood figures in both tonnes and cubic metres then please provide both so that we can develop conversion factors based on actual data.

Large sawlog (Tonnes) Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.	

Large sawlog (Cubic metres) Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.	
Small sawlog (Tonnes) Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres.	
Small sawlog (Cubic metres) Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres.	
Stakewood (Tonnes) Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.	
Stakewood (Cubic metres) Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.	
Pulpwood (Tonnes) Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Exclude: Pulpwood that has been converted to woodchip onsite.	

Pulpwood (Cubic metres) Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Exclude: Pulpwood that has been converted to woodchip onsite.
Roundwood purchased for use as biomass (Tonnes) Roundwood purchased to be used for energy purposes. Exclude bark, woodchip and sawdust purchased as separate products.
Roundwood purchased for use as biomass (Cubic metres) Roundwood purchased to be used for energy purposes. Exclude bark, woodchip and sawdust purchased as separate products.
O1.2 Use of coniferous roundwood removals from privately owned forests in Iroland
Q1.2 Use of conferous roundwood removals from privately-owned forests in Ireland
Please provide the quantity delivered to your premises in tonnes overbark at actual moisture content.
If you have the roundwood figures in both tonnes and cubic metres then please provide both so that we can develop conversion factors based on actual data.
Large sawlog (Tonnes) Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.

Large sawlog (Cubic metres) Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.	
Small sawlog (Tonnes) Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres.	
Small sawlog (Cubic metres) Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres.	
Stakewood (Tonnes) Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.	
Stakewood (Cubic metres) Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.	
Pulpwood (Tonnes) Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Exclude: Pulpwood that has been converted to woodchip onsite.	

Pulpwood (Cubic metres) Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Exclude: Pulpwood that has been converted to woodchip onsite.
Roundwood purchased for use as biomass (Tonnes) Roundwood purchased to be used for energy purposes. Exclude bark, woodchip and sawdust purchased as separate products.
Roundwood purchased for use as biomass (Cubic metres) Roundwood purchased to be used for energy purposes. Exclude bark, woodchip and sawdust purchased as separate products.
Q1.3 Use of non-coniferous roundwood removals from publicly-owned forests in Ireland
Please provide the quantity delivered to your premises in tonnes overbark at actual moisture content. If you have the roundwood figures in both tonnes and cubic metres then please provide both so that we can develop conversion factors based on actual data.
Large sawlog (Tonnes) Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.

Large sawlog (Cubic metres) Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.	
Small sawlog (Tonnes) Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres.	
Small sawlog (Cubic metres) Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres.	
Stakewood (Tonnes) Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.	
Stakewood (Cubic metres) Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.	
Pulpwood (Tonnes) Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Exclude: Pulpwood that has been converted to woodchip onsite.	

Pulpwood (Cubic metres) Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Exclude: Pulpwood that has been converted to woodchip onsite.	
Roundwood purchased for use as biomass (Tonnes) Roundwood purchased to be used for energy purposes. Exclude bark, woodchip and sawdust purchased as separate products.	
Roundwood purchased for use as biomass (Cubic metres) Roundwood purchased to be used for energy purposes. Exclude bark, woodchip and sawdust purchased as separate products.	
Q1.3 Use of non-coniferous roundwood removals from privately-owned forests in Ireland Please provide the quantity delivered to your premises in tonnes overbark at actual moisture content. If you have the roundwood figures in both tonnes and cubic metres then please provide both so that we can develop conversion factors based on actual data.	
Large sawlog (Tonnes) Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.	
Large sawlog (Cubic metres) Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.	

Small sawlog (Tonnes) Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres.	
Small sawlog (Cubic metres) Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres.	
Stakewood (Tonnes) Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.	
Stakewood (Cubic metres) Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.	
Pulpwood (Tonnes) Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Exclude: Pulpwood that has been converted to woodchip onsite.	
Pulpwood (Cubic metres) Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Exclude: Pulpwood that has been converted to woodchip onsite.	

Roundwood purchased for use as biomass (Tonnes) Roundwood purchased to be used for energy purposes. Exclude bark, woodchip and sawdust purchased as separate products.
Roundwood purchased for use as biomass (Cubic metres) Roundwood purchased to be used for energy purposes. Exclude bark, woodchip and sawdust purchased as separate products.

Q.2 Non-roundwood products purchased by your enterprise from forests and enterprises located in Ireland

Please provide the quantity delivered to your premises in tonnes.

Please use the following definitions for the roundwood removals questions:

Large sawlog: Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres. They are used for the manufacture of sawn timber largely for use by the construction industry.

Small sawlog (palletwood): Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres are classified as small sawlog (palletwood). It is suitable for use as packaging and for making garden furniture.

Stakewood: Roundwood with a top diameter of between 7-13 cm and a typical length of between 1.5 and 1.9 metres should be classified as stakewood if it is to be used for stakes and fencing.

Pulpwood: Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Pulpwood is used to produce pulp, door panels, particle board, oriented strand board (OSB), medium-density

fibeboard (MDF), and other fibreboard. Pulpwood that has been converted to woodchip onsite should be entered in the Woodchip category.

Roundwood purchased for use as biomass: Roundwood used for energy purposes should be classified here. Bark, woodchip, and sawdust that were purchased as separate products should not be included here but should be included in the non-roundwood section.

Brash and tree stumps (Tonnes) Brash (lop and top) and tree stumps.
Woodchip (Tonnes) Woodchip removed from the log prior to sale. Include woodchip purchased and used in the production of energy from wood biomass
Sawdust (Tonnes) Sawdust purchased as an input into your manufacturing process and for energy purposes.
Short rotation coppice (Tonnes) Wood grown for energy purposes (e.g. willow).
Post-consumer recovered wood (Tonnes) Includes wood material which is made available for reuse or recycling. May be recovered from packaging materials or building sites and used for material purposes or energy.

Comments, Administration Burden and Contact Details

Please add any comm queries:	nents that would help us to interpret the data provided and avoid further	
How many minutes did i	it take you to collect the data for this form?	
Declaration Please note: Queries or future surveys from the CSO may be directed to the email or phone number provided by you. EQ ANNOTATION 1: Drop down list required for "Position" options include ('Accountant', 'Director', 'Executive', 'Financial Controller', 'Manager', 'Owner', 'Secretary', 'Other')		
Contact	Details	
Name:		
Position:		
Phone:		
Email:		
Website of Enterprise:		
Fircode of Enterprise:		